

Nonlinear Vibrations of Axially-loaded Anti-symmetric Cross-ply Cylindrical Shells

by

Gao Yong

Master of Science in Civil Engineering

1999



**Faculty of Science and Technology
University of Macau**

CHAPTER 5: Results and	TABLE OF CONTENTS	43
5.1: Free Nonlinear Vibrations without Axial Load		44
5.2: Axially-loaded Free Nonlinear Vibrations		48
LIST OF FIGURES		iii
LIST OF TABLES		v
CHAPTER 1: Introduction		1
1.1: Introduction of Theory of Shells		1
1.2: Development of Theory for Laminated Shells		3
1.3: Scope of Present Research		4
CHAPTER 2: Background Knowledge		5
2.1: Nonlinear Elasticity Theory		5
2.1.1 Green's Strain Tensor		5
2.1.2 Kirchhoff's Stress Tensor		8
2.2: Introduction of Laminate Theory		11
2.2.1 General		11
2.2.2 Elastic Properties of A Lamina		12
2.2.3 Elastic Properties of Laminates		15
2.3: Hamilton's Principle		17
2.4: Galerkin's Method		19
2.5: Harmonic Balance Method		22
2.5.1 Introduction		22
2.5.2 Implementation of Harmonic Balance Method		23
CHAPTER 3: Governing Equations Based on Improved Von Karman-Donnell's Nonlinear Theory		26
3.1: Assumptions		27
3.2: Derivation of Governing Equations and Boundary Conditions		28
3.2.1 Derivation of Governing Equations		28
3.2.2 Boundary Conditions		32
3.3: Dimensionless Forms		34
3.2.1 Governing Equations		34
3.2.2 Boundary Conditions		35
CHAPTER 4: Solution Methodology		37

CHAPTER 5: Results and Conclusions	43
5.1: Free Nonlinear Vibrations without Axial Load	44
5.2: Axially-loaded Free Nonlinear Vibrations.....	48
5.3: Conclusions.....	65
REFERENCES.....	66
Figure 2.1.1: A unidirectional lamina	11
Figure 2.2.1: An anti-symmetric cross-ply lamina	12
Figure 2.2.2: Rotation of axes from coordinate system 1-2 to x-y	14
Figure 3.1.1: Shell geometry and coordinate system	27
Figure 5.1.1: Amplitude-frequency responses with different radius-thickness ratio for SS shells (L/R=0.5).....	45
Figure 5.1.2: Amplitude-frequency responses with different radius-thickness ratio for CC shells (L/R=0.5).....	45
Figure 5.1.3: Amplitude-frequency responses with different radius-thickness ratio for CC shells (L/R=1.0).....	46
Figure 5.2.1: Amplitude-frequency responses for axially loaded SS shells (L/R=1.0, R/h=20).....	50
Figure 5.2.2: Amplitude-frequency responses for axially loaded CC shells (L/R=1.0, R/h=50).....	50
Figure 5.2.3: Comparison of frequencies with various loads based on linear theory and improved von Karman-Donnell's nonlinear theory	52
Figure 5.2.4: Effect of the Radius-thickness ratio on linear frequency under axial load.....	53
Figure 5.2.5: Effect of the length-thickness ratio on linear frequency under axial load.....	54
Figure 5.2.6: Effect of the layer number on linear frequency under axial loads.....	54
Figure 5.2.7: Effects of boundary conditions on the frequency at $W_{max}=0$ with various axial loads	55
Figure 5.2.8: Effect of length-thickness and radius-thickness ratio on softening level under different axial loads.....	57